




Tabella dei carichi ammissibili

Campata singola

S mm	K		Peso pannello kg/m ² 0,8 - 0,5	Gruppo colore lamiera esterna							
	Kcal m ² h °C	Watt m ² °C			p = (daN/m ²)	40	60	80	100	120	150
50	0,29	0,34	12,28	I	l =	5,06	4,24	3,72	3,33	3,04	2,70
				II	l =	4,56 5,06	4,24	3,72	3,33	3,04	2,70
				III	l =	3,90 5,06	3,90 4,24	3,72	3,33	3,04	2,70
80	0,20	0,23	13,40	I	l =	6,37 6,72	5,65	4,95	4,45	4,06	3,61
				II	l =	5,52 6,72	5,52 5,65	4,95	4,45	4,06	3,61
				III	l =	4,71 6,72	4,71 5,65	4,71 4,95	4,45	4,06	3,61

Campata multipla

S mm	K		Peso pannello kg/m ² 0,8 - 0,5	Gruppo colore lamiera esterna												
	Kcal m ² h °C	Watt m ² °C			p = (daN/m ²)	40	60	80	100	120	150	60	80	100	120	150
50	0,29	0,34	12,26	I, II, III	l =	6,51	5,50	4,84	4,36	3,99	3,58	5,15	4,60	4,17	3,81	3,41
80	0,20	0,23	13,40	I, II, III	l =	7,75	7,34	6,49	5,88	5,41	4,85				5,15	4,72